

## 2.2 PS + ARVUL

### Self-drilling screw for sandwich panels with EPDM washer



#### Proprieties



Steel

Zinc-plated coating

Hexagonal with washer + ARVUL

#### Characteristics

- Drill point: allows for drilling directly into metallic materials, up to a thickness of 6 mm (straps). No prior drilling required.
- 16 mm diameter EPDM washer to ensure water tightness in panels installed in outdoor enclosures and decking; see "ARVUL" washer technical datasheet.
- Self-tapping thread and zinc-plated coating.
- Hexagonal recess with washer head.
- Installation drill speed: 1000 – 1800 rpm.
- Application: fixing sandwich panels on straps.

#### Benefits



Drill point



Installation with screwdriver

#### Installation data

CODE		PS55060	PS55082	PS55098	PS55115
L: lengths	[mm]	60	82	98	115
Dk: head diameter	[mm]	10.50	10.50	10.50	10.50
C: washer head thickness	[mm]	1	1	1	1
P1: thread ST 5.5	[mm]	1.8	1.8	1.8	1.8
P2: thread ST 6.3	[mm]	1.8	1.8	1.8	1.8
S: spanner	[mm]	8	8	8	8
Drill hole capacity	[mm]	1.5-6.0	1.5-6.0	1.5-6.0	1.5-6.0
Thickness of sandwich panel to be fixed	[mm]	31-45	43-67	54-83	56-100
Installation point code		BOCA008	BOCA008	BOCA008	BOCA008

#### PLAN

