

2.2 AB-ICP

Reinforced isophonic pipe clamp for heavy duty



Benefits



Coating



Zinc-plated

Base Material



Ventilation pipe

Steel pipe

Copper pipe

PVC pipe

Installation data

Code	Ø D (mm)	M	A x B (mm)	C	Fixing range D (mm)	Maximum load recommended (kg)	Characteristics
ABICP060	60	M8/M10	30 x 2,75	17	60 - 65	200	<ul style="list-style-type: none"> • Pipes from Ø60 to Ø315 mm. • Surface coating: electrolytic zinc plated, coating >5 microns. • Steel profile of 2,75 ÷ 4,0 mm thickness • Isophonic, EPDM rubber for insulation, noise and vibration reduction. • According to Technical Building Code, TBC, Basic reports HS and HR. • Side screws with plastic washer to avoid losses. • Reinforced. • Welded nut of M8+M10, M8+M10 and M12+M16
ABICP075	75	M10/M12	30 x 3,0	17	75 - 78	200	
ABICP090	90	M10/M12	30 x 3,0	17	90 - 93	200	
ABICP110	110	M10/M12	30 x 3,0	17	110 - 116	200	
ABICP140	140	M12/M16	40 x 4,0	17	139 - 144	200	
ABICP160	160	M12/M16	40 x 4,0	17	160 - 166	200	
ABICP220	220	M12/M16	40 x 4,0	17	220 - 228	200	
ABICP270	270	M12/M16	40 x 4,0	17	270 - 275	200	
ABICP315	315	M12/M16	40 x 4,0	17	315 - 324	200	

DRAWING

