

2. INSTALLATION DATA

2.1 AB-M6

Pipe clamp M6



Coating		Base Materials		
Yellow zinc plated	Zinc plated	Steel Piping	Copper Piping	Plastic Piping

Installation data

Code	ØB [mm]	Ø B (")	Width	Thickness	Recommended Load (kg)	Characteristics
ABM6008 / ABMZ6008	8	---	10.6	1 ÷ 1.2	70	<ul style="list-style-type: none"> For piping from Ø8 to Ø 63 mm. Surface finish: Yellow zinc plated and zinc plated microns. Steel profile, 1÷1.2 mm thick. Lateral opening for all diameters, for faster installation. Encased M6 nut. Suitable for steel and plastic piping. Suitable for gas, sanitary and electrical installations, etc.
ABM6010 / ABMZ6010	10	1/8	10.6	1 ÷ 1.2	70	
ABM6012 / ABMZ6012	12	1/4	10.6	1 ÷ 1.2	70	
ABM6014 / ABMZ6014	14	---	10.6	1 ÷ 1.2	70	
ABM6015 / ABMZ6015	15	---	10.6	1 ÷ 1.2	70	
ABM6016 / ABMZ6016	16	---	10.6	1 ÷ 1.2	70	
ABM6018 / ABMZ6018	18	3/8	10.6	1 ÷ 1.2	70	
ABM6020 / ABMZ6020	20	---	10.6	1 ÷ 1.2	70	
ABM6022 / ABMZ6022	22	1/2	10.6	1 ÷ 1.2	70	
ABM6025 / ABMZ6025	25	---	10.6	1 ÷ 1.2	70	
ABM6026 / ABMZ6026	26	3/4	10.6	1 ÷ 1.2	70	
ABM6028 / ABMZ6028	28	---	10.6	1 ÷ 1.2	70	
ABM6032 / ABMZ6032	32	1	10.6	1 ÷ 1.2	70	
ABM6035 / ABMZ6035	35	---	11.5	1 ÷ 1.2	70	
ABM6037 / ABMZ6037	37	---	11.5	1 ÷ 1.2	100	
ABM6040 / ABMZ6040	40	---	11.5	1 ÷ 1.2	100	
ABM6042 / ABMZ6042	42	1 1/4	11.5	1 ÷ 1.2	100	
ABM6047 / ABMZ6047	47	---	11.5	1 ÷ 1.2	100	
ABM6050 / ABMZ6050	50	---	11.5	1 ÷ 1.2	100	
ABM6054 / ABMZ6054	54	---	11.5	1 ÷ 1.2	100	
ABM6060 / ABMZ6060	60	2	11.5	1 ÷ 1.2	100	
ABM6063 / ABMZ6063	63	---	11.5	1 ÷ 1.2	100	

DRAWING

