

2. DATOS DE INSTALACION

2.1 AB-RI

Reinforced isophonic pipe clamp M8+M10



Benefits




Coating



Zinc-plated

Base Material



Ventilation pipe

Steel pipe

Copper pipe

PVC pipe

Installation data

Code	Size [mm]	Ø D (mm)	Ø D (")	A x B (mm)	Maximum load recommended(kg)	Characteristics
ABRI018	18	15 - 19	3/8"	18.5x1.75	150	<ul style="list-style-type: none"> • Pipes from Ø18 to Ø1250 mm. • Surface coating: electrolytic zinc plated, coating >3 microns. • Isophonic, EPDM rubber for insulation, noise and vibration reduction. • According to Technical Building Code, TBC, Basic reports HS and HR. • Steel profile of 1.75 ÷ 2.3 mm thickness. • Side screws with plastic washer to avoid losses. • Reinforced. • Welded nut of M8+M10. • Suitable for steel, plastic, copper and ventilation pipes. • Recommended for water supply installations (HSW and CW), drain networks (sanitation), thermal installations (heating, air-conditioning and ventilation systems), compressed air, gas installations, etc. • Service temperature: -30°C ÷ +120°C. • Large sizes available for ventilation pipes.
ABRI022	22	20 - 25	1/2"	18.5x1.75	150	
ABRI028	28	26 - 30	3/4"	18.5x1.75	150	
ABRI035	35	32 - 36	1"	18.5x1.75	150	
ABRI040	40	38 - 43	1 1/4"	18.5x1.75	150	
ABRI048	48	47 - 51	1 1/2"	18.5x1.75	150	
ABRI054	54	53 - 56	-	18.5x1.75	150	
ABRI060	60	60 - 64	2"	18.5x1.75	150	
ABRI070	70	68 - 72	-	18.5x1.75	150	
ABRI075	75	75 - 80	2 1/2"	18.5x1.75	150	
ABRI083	83	81 - 86	-	18.5x1.75	150	
ABRI090	90	87 - 92	3"	18.5x1.75	150	
ABRI100	100	99 - 105	3 1/2"	18.5x1.75	150	
ABRI110	110	107 - 112	-	18.5x2,3	200	
ABRI115	115	113 - 118	4"	18.5x2,3	200	
ABRI125	125	125 - 130	4 1/2"	18.5x2,3	200	
ABRI133	133	132 - 137	-	18.5x2,3	200	
ABRI140	140	138 - 142	5"	18.5x2,3	200	
ABRI150	150	148 - 152	-	18.5x2,3	200	
ABRI160	160	159 - 166	6"	18.5x2,3	200	
ABRI180	180	179 - 184	8"	18.5x2,3	200	
ABRI200	200	199 - 212	-	18.5x2,3	200	
ABRI220	220	215 - 226	-	18.5x2,3	200	
ABRI250	250	245 - 254	-	18.5x2,3	200	
ABRI300	300	299 - 304	-	18.5x2,3	200	
ABRI315	315	314 - 319	-	18.5x2,3	200	
ABRI355	355	354 - 359	-	18.5x2,3	200	
ABRI400	400	399 - 404	-	18.5x2,3	200	
ABRI450	450	449 - 454	-	18.5x2,3	200	
ABRI500	500	499 - 504	-	18.5x2,3	200	
ABRI560	560	555 - 561	-	18.5x2,3	200	
ABRI600	600	599 - 604	-	18.5x2,3	200	
ABRI630	630	625 - 631	-	18.5x2,3	200	
ABRI710	710	705 - 711	-	18.5x2,3	200	
ABRI800	800	799 - 804	-	18.5x2,3	200	
ABRI900	900	899 - 904	-	18.5x2,3	200	
ABRI910	1000	999 - 1.004	-	18.5x2,3	200	
ABRI911	1120	1.115 - 1.121	-	18.5x2,3	200	
ABRI912	1250	1.245 - 1.251	-	18.5x2,3	200	

DRAWING

