

2.15 AB-SA

U-Bolt support



Benefits



Coating



Zinc-plated

Base Material



Steel pipe

Installation data

Code	Size [mm]	H (mm)	L (mm)	A (mm)	T (mm)	Characteristics
ABSA050100	50 x 100	50	100	85	5	<ul style="list-style-type: none"> • Easy, fast and versatile installation. • For M8 and M10 U-Bolts • Fast, safe and resistant installation. • Indicated to be used with M8 U-bolts (with DIN 9021 washer) and M10 U-bolts. • Indicated to fix steel pipes, fixed by means of U-bolts. • General thickness 5 mm. For lengths above 500mm, with 6 mm thickness. • Wide range of sizes, length from 100 mm to 600 mm. • Height, H, of 50 mm and 100 mm.
ABSA050125	50 x 125	50	125	110	5	
ABSA050200	50 x 200	50	200	185	5	
ABSA050300	50 x 300	50	300	285	5	
ABSA050400	50 x 400	50	400	385	5	
ABSA050500	50 x 500	50	500	485	6	
ABSA050600	50 x 600	50	600	585	6	
ABSA100100	100 x 100	100	100	85	5	
ABSA100125	100 x 125	100	125	110	5	
ABSA100200	100 x 200	100	200	185	5	
ABSA100300	100 x 300	100	300	285	5	
ABSA100400	100 x 400	100	400	385	5	
ABSA100500	100 x 500	100	500	485	6	

DRAWING

