

2.14 AB-ZI

U-Bolt



Benefits



Coating



Zinc-plated

Base Material



Steel pipe

Datos de Instalación

Code	M	Ø D (")	A (mm)	B (mm)	C (mm)	Maximum load recommended (kg)	Characteristics
AZIM060125	M6	-	16	14	20	250	<ul style="list-style-type: none"> • Easy, fast and versatile installation. • Suitable to fix steel pipes onto supports and metal strut channels. • Safety installation with 2 nuts in both sides, 4 nuts in total. • Surface coating: electrolytic zinc plated, coating >5 microns. • Great range of sizes. Available diameters: M6, M8 y M10. • Fast and resistant installation.
AZIM060250	M6	1/4"	20	14	20	250	
AZIM060375	M6	3/8"	23,5	15	23	250	
AZIM060500	M6	1/2"	27,5	17	25	250	
AZIM060750	M6	3/4"	33	19	31	250	
AZIM061000	M6	1"	39,5	24	39	250	
AZIM061250	M6	1 1/4"	48,5	24	44	250	
AZIM081500	M8	1 1/2"	56,5	26	48	350	
AZIM082000	M8	2"	68,5	26	53	350	
AZIM082250	M8	2 1/4"	83	35	63	350	
AZIM082500	M8	2 1/2"	83	35	71	350	
AZIM083000	M8	3"	99	35	76	350	
AZIM083500	M8	3 1/2"	112	35	82	350	
AZIM084000	M8	4"	125	35	87	350	
AZIM084500	M8	4 1/2"	140	40	100	350	
AZIM085000	M8	5"	152	40	105	350	
AZIM086000	M8	6"	179	40	118	350	
AZIM103000	M10	3"	100	45	66	350	
AZIM103500	M10	3 1/2"	110	50	94	350	
AZIM104000	M10	4"	125	55	97,5	350	
AZIM105000	M10	5"	150	55	108	350	
AZIM106000	M10	6"	170	55	125	350	
AZIM108000	M10	8"	230	55	148	350	

DRAWING

